

FUHR

International, L.L.C.
Specialty Paint &
Wood Coatings

High Quality Water based
Wood Finishes

BETTER GRADE

Product Number:
9560

High Solids White Primer

Summer 2002

A high solids, lower cost, waterbased acrylic primer designed for various interior wood substrates. Typical uses include shutters, trim, doors, moldings, cabinetry, furniture and many other interior surfaces requiring a primer prior to finishing. Compatible with a wide variety of wood substrates.

Typical application is one to two coats depending on quality desired. Typical dry time to sand in ambient conditions is approximately 10 minutes. Dry time to sand can easily be accelerated with the use of heat and air movement achieving a sand able surface in only minutes. Sanding between coats and prior to topcoat application is recommended for optimum performance but not required in most cases. 9560 sands very well with 320 grit sandpaper and other similar abrasives. Compatible with most all finishing systems and equipment types, hand spray or automated.

PRODUCT DATA & SPECIFICATIONS

Appearance & Odor: White liquid, mild odor	VOC content by #: .15#/gallon
Evaporation Rate: Slower than ether	VOC content by G/l: 18 Grams / liter
Solubility in Water: Soluble	VHAP content: 0
Specific Gravity: < 1.61	VOC % Solids content: .0001# /solids/gallon
Weight per Gallon: 13.44 #	Flash Point: Non-combustible
Solids by Weight: 9.63 #	Flammability: Not applicable
Solids by Volume: 71.67 %	Viscosity: # 4 Zahn Cup, 15-18 seconds

Substrate Preparation: Thoroughly clean the surface to be primed of all dirt, grease, oil etc. Product should be sanded prior to application of 9560. Optimum performance is achieved by pre-sanding substrates to 220 grit or higher.

Application: Apply in wet coats measured at approximately 3-5 wet mils .

Cleanup: Flush all equipment with water both before and after use of 9560. Build-up may be removed with a cleaner solution such as 330 Universal Cleaner & Stripper. Flushing with water is necessary after the use of any cleaning agent to avoid contamination.

Featured Benefits

* Haps Free * No Flash Point * Excellent Mar Resistance * Great Blocking Resistance *
* High Solids * Water Clean-Up * Fast Drying * High Hardness * Minimal to No Grain Raising *

DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033