

**WATERBORNE PIGMENTED BASECOAT** 

# **AQUAPRIME®**



# **AQUAPRIME®** Solid performance

## WATERBORNE PIGMENTED BASECOAT

AQUAPRIME delivers very high build and provides a good base on hard woods, soft woods and MDF. It performs like a solvent based primer with minimal grain raising. High solids formulation - 65%; it has excellent hold out and sands easily and quickly. AQUAPRIME is available for use under all Chemcraft waterborne and solvent borne topcoats.

#### **AQUAPRIME Distinct Advantages Over the Competition**

- · Can be used under all Chemcraft systems including UV
- High solids: 66% by weight / 48% by volume
- Excellent sandability
- Impressive hold out and film build minimal shrinkage
- · High hide and good filling capabilities
- · Bright white
- Fast stack time 2 hours
- Efficient for production
- Single component no catalyst or waste

### **Other Advantages**

- Waterborne
- · Ready-to-use viscosity Fast dry
- · Water clean up
- · Low odor
- · Can be used to prime wood or MDF
- Will hide MDF edges in a single pass
- · Cost competitive compared to solvent primers
- HAPs compliant
- Low VOC <65 grams per liter</li>
- 275/550 VOC compliant
- Long shelf life 6 months when stored at ambient conditions
- Performs very well when force dried
- · Can be tinted with 888 and 896 tints
- · Also available in black and neutral

#### **AQUAPRIME** alone or with Chemcraft approved systems

#### Hot / Cold Check Resistance: ASTM D1211

Purpose: Test the ability of the finish to withstand hot  $(120^{\circ} \text{ F} / 50^{\circ} \text{ C})$  & cold  $(-5^{\circ} \text{ F} / -20^{\circ} \text{ C})$  cycles for prolonged periods. Coating surpasses 10 cold check cycles. Passes with a Perfect Rating of 10.

Cross Hatch: ASTM D3359

Purpose: Test the finish's adhesion to various substrates. Uses ASTM Cross Hatch Specific Rating Scale. Top rating of 5B.

Blocking: ASTM D2793

Purpose: Test the ability of the finish to withstand any finish defects from stacking or packing after 4 hours of drying time. Passes with a Perfect Rating of 10.



Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033







