

3M Construction & Home Improvement Markets

Product Information Sheet

October 2006

Scotch® Masking Tape for Production Painting #2020



Scotch® Masking Tape for Production Painting #2020 is a high adhesion, general purpose masking tape for for quick projects or on hard-to-stick or rough surfaces. It can also be used for holding, bundling, sealing, and other jobs where a pressure-sensitive tape is needed.

Product Characteristic	Value
Backing	Natural Colored Crepe Paper
Adhesive	Rubber
Standard Roll Length	60 yards (54.8 m)
Color	Tan

Typical Physical Properties	Value	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.
Adhesion to Steel	35 oz./in.	ASTM D-3330
Tensile Strength	20 lbs./ in.	ASTM D-3759
Elongation at Break	9 %	ASTM D-3759
Total Thickness	0.0052 in. (0.13 mm)	ASTM D-3652

Features/Advantages Benefits:

Feature (HAS)	Advantage (WHICH MEANS)	Benefit (SO THAT)
Rubber Adhesive	Instant Adhesion	Sticks easily to the surface and helps resist tape lifting or curling /helps reduce labor
	Good Holding Power	Helps resist lifting or curling/helps reduce rework. This product is typically used at room temperature, but will function up to 150°F (65°C) for up to 1 hour.
Crepe Paper Backing	Conformability	Easy handling/helps reduce overall project time
Backing Saturant	Easy Tear	Good handling/helps reduce waste
	Solvent and Moisture Resistance	Resists paint bleed-through/helps reduce rework
Backsize Treatment	Controlled Unwind	Easy to use/smooth unwind

Warnings:

- Do not use on wallboard, wallpaper, or other delicate surfaces.
- Do not subject to outdoor exposure.
- Do not use on wood floors.
- Do not use on poorly bonded surfaces.
- Test before use.
- Made from Natural Rubber.

**3M Construction and Home
Improvement Markets Division**
3M Center, Building 251-1C-09
St. Paul, MN 55144-1000

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

Limitation of Liability: 3M SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS, OR REVENUES) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS 3M PRODUCT, WARRANTY, OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a 3M officer..

3M, Scotch, and the Plaid Design are trademarks of 3M Company.
© 3M 2006

DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033