

Information Sheet

Product Label Text
B730-1365

H. Behlen Wool-Lube

is a specially formulated concentrated liquid rubbing lubricant.

Wool-Lube is *non-toxic and non-flammable*.

DIRECTIONS:

SHAKE WELL BEFORE USING.

Wool-Lube may be mixed 1-1 with water.

LEVELING BURN-IN REPAIRS:

Once a burn-in has been leveled and allowed to cool or harden, apply a small amount of Wool-Lube to 800 waterproof sandpaper wrapped around a cork sanding block.

Begin leveling with the grain using light even strokes (**be careful not to cut through surrounding color.**)

After a few strokes, stop and examine repair. Continue sanding until repair is level with surrounding surface.

Wipe off excess Wool-Lube with a water dampened cloth.

Adjust sheen of repair with new topcoat.

•••••

KEEP OUT of REACH of CHILDREN
Avoid Contact with Eyes

RUBBING FINISHES:

Follow coating manufacturer's dry time when rubbing new finishes.

Place a small amount of **H. Behlen Wool-Lube** on steel wool, an abrasive pad or waterproof sandpaper.

Rub in the direction of the grain with smooth even strokes.

Reapply Wool-Lube as needed until desired rubbing effect is achieved.

Wipe off excess Wool-Lube with a water dampened cloth.

Wool-Lube will not cause adhesion problems if recoating.

Apply wax or polish as desired to protect the finish.

Additional Notes:

A more aggressive cutting action will result when Wool-Lube is mixed with water.

*For Best Results when rubbing out a finish, make sure the finish is **fully cured** and not just dry. Most air dry finishes need a full 21-30 days under good conditions to achieve maximum cure and hardness. The harder the finish the more predictable and consistent the result.*