

# StanZoil NL-34/334

## DESCRIPTION AND GENERAL PROPERTIES

- **Material** Neoprene
- **Length (inches)** 12
- **Wrist** Straight cuff
- **Colour/Color** Black / Blue
- **Interior finish** Textile support
- **Exterior finish** Non-slip grip
- **Size / EAN** 6 7 8 9
- **Packaging** 12 pairs/box - 72 pairs/carton



## PERFORMANCE RESULTS

### Certification category



X2XXXX



ACJKL




3121

### Legends



**MECHANICAL HAZARDS EN 388**

PERFORMANCE LEVELS



**LOW CHEMICAL PROTECTION EN 374**



**MICRO-ORGANISMS EN 374**




**RADIOACTIVE CONTAMINATION EN 421**



**HEAT AND FIRE EN 407**

PERFORMANCE LEVELS




**SPECIFIC CHEMICAL PROTECTION EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS EN 511**

PERFORMANCE LEVELS



For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**  
PROFESSIONAL

[www.mapa-pro.com](http://www.mapa-pro.com)

## DESCRIPTION AND GENERAL PROPERTIES

- Soft, absorbent interlock knit cotton liner adds comfort, easy on-off, high-and low-temperature protection.
- 1.5 AQL - Quality Assurance

## MAIN FIELDS OF USE

### Mechanical industry

- Maintenance in wet environments (water, oil, greases, hydrocarbons)

### Chemical industry

- Handling and transporting chemicals

### Petroleum industry

- Handling

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
  - It is not recommended for persons sensitized to natural latex proteins and dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.  
Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.  
Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging at a temperature not below 5°C.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (dilutents, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : using the gloves or submitting them to another cleaning or laundering process that is not specifically recommended can alter their performance levels

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

### Food contact US

FDA 21CFR 177.2600

## LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.  
This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).