

# Fix-It DUCTape™

## UTILITY GRADE DUCT

# INTERTAPE POLYMER GROUP®

## TECHNICAL DATA SHEET

### DESCRIPTION

Polyester (PET) cloth / polyethylene (PE) film with an aggressive pressure sensitive natural rubber adhesive combines to provide a quality utility product. Conformable to irregular surfaces.

### PRODUCT APPLICATIONS

Packaging, wrapping & sealing, binding & bundling, and general maintenance.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	PE Coated Cloth
<b>Adhesive</b>	Natural Rubber / Resin
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	17 (74 N/25mm)
<b>Elongation</b> (% at break)	15
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	41 (11.2 N/25mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-105	13.5 (3.7 N/25mm)
<b>Total Thickness</b> (mils) PSTC-133	7.0 (0.178mm)
<b>Temperature Resistance</b>	+32°F ~ +160°F (0°C ~ +71°C)
<b>Color</b>	Silver



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 6/11

