## Mohawk

## **Product Data Sheet**

Finishing Products, Inc.

SILICONE WASH	DILLICOT (L. TTIDIT
---------------	---------------------

M712-320 AVAILABLE IN 1 GALLON

-----

**Product Description:** Mohawk Silicone Wash is a wash that helps to remove silicone residue caused by polishes and waxes. Silicone Wash also minimizes fish-eye problems from silicones. An excellent afterwash for removers.

\_\_\_\_\_

## Characteristics:

Weight per gallon:  $7.26 \pm 0.11$ bs/gal

Flashpoint: 45F/7C

Volatile Organic Compounds (VOC): 870 GPL

Package Life: 3 years

Spec. Gravity: .87 ± 0.01 Boiling Range: 232F/111C

Air Quality Data: Photochemically Reactive

Hazardous Air Pollutants: 100 %

HMIS:

Health: 1 Flammability: 3 Reactivity: 0

Personal Protection: B

\_\_\_\_\_

## Specifications:

Directions: Remove the old finish with either Mohawk Finish Remover #2 or #3. Apply Silicone Wash with burlap or other coarse weave fabric, wiping the entire surface. Keep fabric thoroughly saturated and change fabric as needed.

If surface is to be finished without removing the old finish, dampen a cloth with Silicone Wash and wipe over entire surface twice. Use another cloth and repeat the process. Turn cloth often.

Safety Cautions: Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.

Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380 Fax: 518-842-3551

DISTRIBUTED BY: Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033