

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Universal Colors

M562-Series

Available in quarts & 4fl. oz. assortment

#### Product Description:

Advantages:

1. Fineness of grind for optimum color value and gloss development.
2. Viscosity stability on aging.
3. High pigment loading for maximum color intensity.
4. Clean bright colors with no fillers added to "muddy" tones.
5. Compatible in most solvent systems. Always trial for compatibility and desired affect before using.
6. Colors may be intermixed.

Product Limitations:

1. DO NOT use Universal Colors in:
  - a) Water base systems.
  - b) Alcohol based systems such as shellac or spirit varnish.
  - c) Systems containing high percentages of plasticizer such as glaze products.
2. Use Universal Colors for **tinting** only.

#### Characteristics:

Weight per gallon: 8.17 - 10.97 lbs/gal\*

Flashpoint: 108F/42C

Dry time: Air dry @ 72F

Adding Universal Colors in tinting amounts to lacquers or other products will not adversely affect the drying time of the product.

Volatile Organic Compounds (VOC):

Not to exceed 352 GPL, 2.9 lb/gal

Spec. Gravity: .98 - 1.32\*

Boiling Range: 318F/159C

Non Volatile (wt): 68 - 79%\*

Package Life: 3 years

Hegman Grind: 7 to 8

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: None

\* Depending upon color

All values theoretical; not intended to be exact

QC specifications

HMIS: Health – 2, Flammability – 3, Reactivity – 0, Personal Protection - X

**Specifications:** Universal Color system is designed for tinting purposes only. Excess additions will retard dry time. Always consult the product information that you are tinting to assure that you do not exceed the recommended tint colorant addition of the product.

**Directions:** Base product should be mixed well to insure uniformity before adding M562 colorants. Add small quantities with thorough mixing until color effect is achieved.

**Safety and Other Precautions:** Read MSDS for precautions before using product.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545