Mohawk

Finishing Products, Inc.

Product Data Sheet

WAX WASH

M712-190 AVAILABLE IN QUARTS, GALLONS

Product Description: Mohawk Wax Wash is a combination of solvents that will remove wax, oil and foreign materials from most surfaces in one application. The presence of wax, oil or foreign material can retard drying or cause defects in finishing topcoats. Prior to applying a new finish or repair, clean surface with Wax Wash. Ideal for furniture, appliances, woodwork, and other finished surfaces.

Characteristics:

Weight per gallon: 6.82 ± 0.1 lbs/gal Flashpoint: 45F/7C Volatile Organic Compounds (VOC): 817 GPL Package Life: 3 years Spec. Gravity: .82 ±0.01 Boiling Range: 230F/110C Air Quality Data: Photochemically Reactive Hazardous Air Pollutants: 27 %

HMIS:

Health: 1 Flammability: 3 Reactivity: 0 Personal Protection: B

Specifications:

Directions: Fold a clean, absorbent cloth into several layers and then saturate the cloth with Wax Wash. Briskly wipe over surface, constantly turning the cloth while wiping, so that wax or oils will absorb into the cloth rather than be redistributed on the surface. Then wipe off residue with a clean dry cloth and allow to dry for a few minutes before the application of a finish or before repolishing.

Safety Cautions: Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.

Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

<u>MSDS</u>: If Material Safety Data Sheet is required, contact: Mohawk Finishing Products, Inc. 4715 STHWY 30 Amsterdam, NY 12010-7417 Phone: 518-843-1380 Fax: 518-842-3551

Rev. 10/09/00

DISTRIBUTED BY: Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033