CSI Div. 06910

SPECIALTY

ROTTEN STONE

Polishing Compound For Wood

MANUFACTURER:

Empire Blended Products, Inc. 250 Hickory Lane • Bayville, NJ 08721 (732) 269-4949 • Fax (732) 269-0497 www.empireblended.com

PRODUCT DESCRIPTION:

RAINBOW ROTTEN STONE is an extremely fine abrasive powder which when mixed with oil can be used to create a hand rubbed, polished finish for dull, scratched wood surfaces. It is used as a follow up polishing agent after a RAINBOW PUMICE STONE rubdown to achieve a higher sheen than would be possible by using just PUMICE STONE. ROTTEN STONE can be used as a fine polishing agent for finishing painted, lacquered or varnished surfaces to a uniform high gloss, non-glare appearance. Other uses include removing tarnish and polishing pewter and other low luster metal surfaces.

USES:

- Polishing wood surfaces
- Polishing pewter and other low luster metal surfaces
- Removing tarnish from metal

ADVANTAGES:

Uniform particle size

APPLICATION:

Surface Preparation:

Wood surface to be polished should be clean and thoroughly dry.

Mixing:

No mixing is necessary.





Directions:

Wood polish

POLISHING COMPOUND

Saturate rubbing felt or plain soft cloth with light oil. Dip it in *ROTTEN STONE* and shake off the excess. Apply, using uniform pressure over a small area, using approximately 6-8 strokes, always rubbing with the grain of the wood. Wipe off the excess *ROTTEN STONE* with a clean, oil saturated cloth. Remove oil with a plain, dry cloth. This will give a satiny finish. If a gloss finish is desired, use water instead of oil. The oil rubdown is slower than water, but both processes are very effective. Finish the job with a final rubbing of dry *ROTTEN STONE*.

Directions:

Metal Polish

Mix ROTTEN STONE with household mineral oil or cooking oil to a creamy consistency. Using a damp sponge or cloth, apply to metal. Before polish dries, rinse with lukewarm water. Finish the job with a final rubbing of dry ROTTEN STONE or RAINBOW COMMERCIAL WHITING.

Coverage:

Amount of surface area polished will vary with the type and condition of the wood and the finish desired.

Packaging:

Available in 1 pound boxes with sealed plastic bags (12 per carton), 5 pound boxes with sealed plastic bags (6 per carton) and 25 pound and 50 pound multiwall paper bags with moisture barrier. Color: Light gray

TECHNICAL DATA:

Particle Size...... 400 mesh pH7.65

LIMITATIONS:

Care should be taken when rubbing so as not to create scratching on the surface.

CAUTION:

Keep Out Of Reach Of Children.

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either Empire Blended Products or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.

> DISTRIBUTED BY: Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033