




Latex

Thicker design for enhanced protection



**3x thicker than our
standard latex gloves¹**



FEATURES AND BENEFITS:

Three Times Thicker Than Our Standard Latex Gloves¹

The thickest Microflex® latex glove in the palm and finger areas, for additional protection when safety cannot be compromised. Provides a secure barrier against harmful chemicals – including solvents.

Textured Fingers for Reliable Grip

In wet or dry conditions, textured fingers ensure a consistent, reliable grip throughout the work day.

Extra Coverage

Extended, beaded cuff offers enhanced protection when extra coverage is needed over the wrist and forearm.

Exceeds Quality Standards

Pinhole rates well below FDA standards for exam gloves. Meets the requirements for NFPA 1999 Standard on Protective Clothing for Emergency Medical Operations, 2013 edition.

¹Based on powder-free Latex Exam gloves with 6 mil fingertip thickness (such as Evolution One® and SafeGrip®), Safegrip®/63-893 fingertip thickness runs 17.3-17.7 mils.

Industries

- Automotive
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices)
- Electronics
- Emergency Medical Services
- Healthcare
- Laboratory

Applications

- Analytical testing/measurements
- Assembly and inspection of oil-coated pieces
- Cleaning
- Crime scene evaluation
- Filtration Processes
- Food and dairy processing
- Handling small parts
- Healthcare
- Janitorial and maintenance work
- Maintaining equipment & instruments
- Packaging
- Paint and spray shops
- Printing industry
- Protection from blood and other bodily fluids
- Re-fueling
- Warehousing

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	SafeGrip®
Material	Latex
Color	Blue
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Textured Fingertips
Cuff	Beaded Cuff
Manufacturing/QMS Audit Standards	ISO 13485
Regulatory/Standards Compliance	ASTM D3578, US NFPA, US QSR/FDA 510(K) MEDICAL (EXAMINATION) GRADE, COMPLIANT WITH U.S. FOOD CONTACT REGULATIONS
Packaging	50 gloves per dispenser, 10 dispensers per shipper carton, 500 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES				TESTING METHOD
	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	ASTM D3767/EN 420
Length (mm)	295	295	295	295	
Average Palm Width (mm)	86	95	106	115	
Freedom from Holes (Inspection level I)	1.5 AQL				ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.28) / (mil : 11)				ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING		
Ultimate Tensile Strength	> 34 Mpa		> 28 Mpa		ASTM D 412-06a
Elongation at Break (%)	> 750		> 600		ASTM D 412-06a
Force at break (N)	30		20		EN 455-2

ORDERING INFORMATION:

	SIZE	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
SafeGrip®	REORDER NO.	SG-375-S	SG-375-M	SG-375-L	SG-375-XL

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

Warning: This product contains natural rubber latex, which may cause allergic reactions in sensitive individuals.

For additional information visit us at www.ansell.com, or call us at 1-877-750-6110

Ansell
111 Wood Avenue South
Suite 210
Iselin, NJ 08830
USA

Ansell
105 Lauder
Cowansville, QC J2K 2K8
Canada



DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033

Ansell