



Woodworking Glues Construction Adhesives Caulks & Sealants Flooring Products

Titebond Original Wood Glue

Titebond Original Wood Glue is the industry standard for woodworking. It provides a strong initial tack and fast speed of set to reduce clamp time. It also develops a bond stronger than the wood itself, offers excellent sandability and is unaffected by finishes.

Titebond Original can help any woodworker achieve professional-looking results. It is ideal for wood, hardboard, particleboard, leather, cloth and most other porous materials. Titebond Original is easy to use, non-toxic and cleans up with water.



CONFORMS TO ASTM D-4236

Ordering Information	Product Features	Physical Properties	Application Guidelines	Limitations	Caution Statement
----------------------	------------------	---------------------	------------------------	-------------	-------------------

Application Temperature

Above 50°F.

Open Assembly Time

4-6 minutes (70°F./50%RH)

Total Assembly Time

10-15 minutes (70°F./50%RH)

Minimum Required Spread

Approximately 6 mils or 250 square feet per gallon

Required Clamping Pressure

Enough to bring joints tightly together (generally, 100-150 psi for softwoods, 125-175 psi for medium woods and 175-250 psi for hardwoods)

Method of Application

Plastic bottles for fine applications; glue may also be spread with a roller spreader or brush.

Cleanup

Damp cloth while glue is wet. Scrape off and sand dried excess.

OUR PRODUCTS



OUR BRANDS

DISTRIBUTED BY:
Pro Wood Finishes
 14622 Southlawn Lane
 Rockville MD 20850
 Ph: (301) 424-3033