



Woodworking Glues    Construction Adhesives    Caulks & Sealants    Flooring Products

## Titebond II Premium Wood Glue

Titebond II Premium Wood Glue is the only leading brand, one-part wood glue that passes the ANSI Type II water-resistance specification. It is ideal for exterior woodworking projects, including outdoor furniture, birdhouses, mailboxes, planters and picnic tables.

Titebond II Premium provides a strong initial tack, fast speed of set, superior strength and excellent sandability. It is FDA approved for indirect food contact (cutting boards) and is ideal for radio frequency (R-F) gluing systems.



CONFORMS TO ASTM D-4236

Ordering Information	Product Features	Physical Properties	Application Guidelines	Limitations	Caution Statement
----------------------	------------------	---------------------	------------------------	-------------	-------------------

**Application Temperature**

Above 55°F.

**Open Assembly Time**

3-5 minutes (70°F./50%RH)

**Total Assembly Time**

10-15 minutes (70°F./50%RH)

**Minimum Required Spread**

Approximately 6 mils or 250 square feet per gallon

**Required Clamping Pressure**

Enough to bring joints tightly together (generally, 100-150 psi for softwoods, 125-175 psi for medium woods and 175-250 psi for hardwoods)

**Method of Application**

Plastic bottles for fine applications; glue may also be spread with a roller spreader or brush.

**Cleanup**

Damp cloth while glue is wet. Scrape off and sand dried excess.

**OUR PRODUCTS**



**OUR BRANDS**

**DISTRIBUTED BY:**  
**Pro Wood Finishes**  
 14622 Southlawn Lane  
 Rockville MD 20850  
 Ph: (301) 424-3033