



Woodworking Glues    Construction Adhesives    Caulks & Sealants    Flooring Products

## Titebond III Ultimate Wood Glue

Titebond III Ultimate Wood Glue is the first one-part, water cleanup wood glue ever offered that is proven waterproof. The waterproof formula passes the ANSI/HPVA Type I water-resistance specification and offers superior bond strength, longer open assembly time and lower application temperature.

Titebond III is non-toxic, solvent free and cleans up with water - safer to use than traditional waterproof wood glues. It provides strong initial tack, sands easily without softening and is FDA approved for indirect food contact (cutting boards). The ultimate in wood glues - ideal for both interior and exterior applications.



CONFORMS TO ASTM D-4236

Ordering Information	Product Features	Physical Properties	Application Guidelines	Limitations	Caution Statement
----------------------	------------------	---------------------	------------------------	-------------	-------------------

**Application Temperature**

Above 47°F.

**Open Assembly Time**

8-10 minutes (70°F./50%RH)

**Total Assembly Time**

20-25minutes (70°F./50%RH)

**Minimum Required Spread**

Approximately 6 mils or 250 square feet per gallon

**Required Clamping Pressure**

Enough to bring joints tightly together (generally, 100-150 psi for softwoods, 125-175 psi for medium woods and 175-250 psi for hardwoods)

**Method of Application**

Plastic bottles for fine applications; glue may also be spread with a roller spreader or brush.

**Cleanup**

Damp cloth while glue is wet. Scrape off and sand dried excess.

OUR PRODUCTS



OUR BRANDS

**DISTRIBUTED BY:**  
**Pro Wood Finishes**  
 14622 Southlawn Lane  
 Rockville MD 20850  
 Ph: (301) 424-3033