



Woodworking Glues Construction Adhesives Caulks & Sealants Flooring Products

Titebond III Ultimate Wood Glue

Titebond III Ultimate Wood Glue is the first one-part, water cleanup wood glue ever offered that is proven waterproof. The waterproof formula passes the ANSI/HPVA Type I water-resistance specification and offers superior bond strength, longer open assembly time and lower application temperature.

Titebond III is non-toxic, solvent free and cleans up with water - safer to use than traditional waterproof wood glues. It provides strong initial tack, sands easily without softening and is FDA approved for indirect food contact (cutting boards). The ultimate in wood glues - ideal for both interior and exterior applications.



CONFORMS TO ASTM D-4236

Ordering Information	Product Features	Physical Properties	Application Guidelines	Limitations	Caution Statement
----------------------	------------------	---------------------	------------------------	-------------	-------------------

Type: Advanced Proprietary Polymer

State : Liquid

Color : Tan

Dried Film: Light brown

Solids : 52%

Viscosity : 4,200 cps

Storage Life : 24 months in tightly closed containers below 75°F.

*Chalk temperature indicates the lowest recommended temperature at which the glue, air and materials can be during application, to assure a good bond.

Calculated VOC: 9 g/L

Weight Per Gallon : 9.22 lbs

Chalk Temperature: * Approximately 45°F

Flashpoint : > 200°F.

Freeze/thaw Stability : Stable

pH : 2.5

BOND STRENGTH ASTM D-905 (ON HARD MAPLE)

Temperature	Strength	Wood Failure
Room Temperature	4,000 psi	57%
150°F Overnight	800 psi	0%

OUR PRODUCTS



OUR BRANDS

