



DISTRIBUTED BY:
Pro Wood Finishes
 14622 Southlawn Lane
 Rockville MD 20850
 Ph: (301) 424-3033

QUICKSTAIN®

ALKYD WIPING STAIN

1U.1000

Features

- Tint Base For Custom Colors
- Ready To Use Formulation
- Uniform Penetration
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying For Lacquers

General Description

Lenmar® QuickStain® Alkyd Wiping Stains have been uniquely designed for the professional woodworker in the Flooring, Furniture & Cabinet Industry and are formulated for ease of use, and color stability. The major benefits of this stain include: a natural / clear tint base for custom tinting with industrial colorants, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading.

Recommended For

Kitchen Cabinets, Wood Floors, Furniture, Window & Door Trim, Baseboards & Molding, Interior Doors & Hand Rails.

Limitations

- For floor applications, wait 2-3 hours before proceeding with topcoats.

Product Information

Product Information																																																																						
Colors — Standard: N/A	Technical Data <table border="1"> <thead> <tr> <th colspan="2"></th> <th>Natural/Clear Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Solids</td> <td></td> <td>10.3%</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>8.9%</td> </tr> <tr> <td>Coverage per Gallon at 1 mil DFT</td> <td></td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td></td> <td>– Dry</td> <td>N/A</td> </tr> <tr> <td>Dry Time @ 75 °F (23.8 °C) @ 50% RH</td> <td>– Tack Free</td> <td>15 Minutes</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>30 Minutes</td> </tr> <tr> <td colspan="3">High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Oxidation</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>18 – 22 Seconds (#2 Zahn)</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>100 °F (37.8 °C)</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min.</td> <td>68 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90 °F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>1A.137 Mineral Spirits</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>7.33 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90 °F</td> </tr> <tr> <td colspan="3"> Volatile Organic Compounds (VOC) 736 Grams/Liter 6.14 Lbs./Gallon </td> </tr> </tbody> </table>			Natural/Clear Base	Vehicle Type		Alkyd	Pigment Type		N/A	Weight Solids		10.3%	Volume Solids		8.9%	Coverage per Gallon at 1 mil DFT		N/A	Recommended Film Thickness	– Wet	N/A		– Dry	N/A	Dry Time @ 75 °F (23.8 °C) @ 50% RH	– Tack Free	15 Minutes		– To Recoat	30 Minutes	High humidity and cool temperatures will result in longer dry, recoat and service times.			Dries By		Oxidation	Viscosity		18 – 22 Seconds (#2 Zahn)	Flash Point		100 °F (37.8 °C)	Gloss / Sheen		N/A	Surface Temperature at Application	– Min.	68 °F		– Max.	90 °F	Thin With		Do Not Thin	Clean Up Thinner		1A.137 Mineral Spirits	Weight Per Gallon		7.33 lbs	Storage Temperature	– Min.	50 °F		– Max.	90 °F	Volatile Organic Compounds (VOC) 736 Grams/Liter 6.14 Lbs./Gallon		
		Natural/Clear Base																																																																				
Vehicle Type		Alkyd																																																																				
Pigment Type		N/A																																																																				
Weight Solids		10.3%																																																																				
Volume Solids		8.9%																																																																				
Coverage per Gallon at 1 mil DFT		N/A																																																																				
Recommended Film Thickness	– Wet	N/A																																																																				
	– Dry	N/A																																																																				
Dry Time @ 75 °F (23.8 °C) @ 50% RH	– Tack Free	15 Minutes																																																																				
	– To Recoat	30 Minutes																																																																				
High humidity and cool temperatures will result in longer dry, recoat and service times.																																																																						
Dries By		Oxidation																																																																				
Viscosity		18 – 22 Seconds (#2 Zahn)																																																																				
Flash Point		100 °F (37.8 °C)																																																																				
Gloss / Sheen		N/A																																																																				
Surface Temperature at Application	– Min.	68 °F																																																																				
	– Max.	90 °F																																																																				
Thin With		Do Not Thin																																																																				
Clean Up Thinner		1A.137 Mineral Spirits																																																																				
Weight Per Gallon		7.33 lbs																																																																				
Storage Temperature	– Min.	50 °F																																																																				
	– Max.	90 °F																																																																				
Volatile Organic Compounds (VOC) 736 Grams/Liter 6.14 Lbs./Gallon																																																																						
— Tint Bases: 1U.1000, Natural/Clear Base Can be tinted with Industrial Colorants																																																																						
— Special Colors: Contact your Dealer/Distributor.																																																																						
Certification & Qualifications: VOC compliant in federally regulated areas only The products supported by this data sheet contain a maximum of 750 grams per liter VOC /VOS (6.26 lbs/gal.) excluding water & exempt solvents.																																																																						
Technical Assistance: Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit www.lenmar-coatings.com																																																																						

QuickStain Alkyd Wiping Stain 1U.1000

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain® Alkyd Wiping Stain by spray, natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 30 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. Check adhesion before proceeding with this type of application. See characteristics for finish options and recommended dry times. For floor applications, wait 2-3 hours before proceeding with topcoats.

Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120 – 150 grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same color. Test color before proceeding. Color intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings

Clean up

Clean up with 1A.137 Mineral Spirits.

Environmental Health & Safety Information

DANGER!

Causes skin irritation

Suspected of causing cancer

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an approved waste disposal plant.

DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN

THIS PRODUCT IS INTENDED FOR SHOP OR OEM APPLICATION ONLY.

READ ALL DIRECTIONS BEFORE USE.
UNDERSTAND **ALL** DANGERS WITH THIS
PRODUCT PRIOR TO USE.

**Refer to Safety Data Sheet for
additional health and safety information.**