

Mohawk Finishing Products

A Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Designer Series Stain

M547- all colors

Available in gallons

Product Description: Mohawk Designer Series Stains are unique colors that enable deep, rich, intense color development in one application that previously may have taken multiple color steps to achieve. These rich stains can be sealed in as little as 30 minutes. Designer Series Stains are available in 6 colors and are packaged in single gallon containers. The stain colors may be blended together to create custom colors.

Advantages:

1. Solvent based pigmented wiping stains
2. Available in 6 strong, deep colors
3. Average of 50% more pigment than M545 stains
4. Similar open and dry time to M545 Stains
5. Enables deep, rich, intense color development in one application
6. Stain colors may be blended together to create custom colors

Characteristics:

Weight per gallon: 7.86 – 8.65 lbs/gal*

Solids % (wt): 20.89 – 46.77*

Solids % (vol): 13.58 – 33.56*

Dry time: Air dry @ 72° F, 35% relative humidity

To touch: 7 minutes

To handle: 15 minutes

To topcoat: 30+ minutes

VOC's (coating): 4.59 – 6.23 lbs/gal (551.13 – 748.69 g/l)*

VOC's (material): 4.59 – 6.23 lbs/gal (550.82 – 748.62 g/l)*

VHAP's: 0.0542 – 0.1409 lbs VHAP's/lbs solids*

Coverage: 400 square ft/gal

Package Life: 3 years

All values theoretical; not intended to be exact QC specifications.

*Individual stains fall within given range, see MSDS for specific values for individual formulas.

HMIS: Health – 2, Flammability – 2, Reactivity – 0, Personal Protection – X

Specifications:

Directions: STIR OR SHAKE WELL BEFORE USING. Apply generously by wiping, brushing or spraying. Allow to flash off momentarily, then use a clean absorbent cloth to remove excess and wipe to color. Use caution to not leave excess stain on the surface, which could adversely affect adhesion. Stain colors may be intermixed with other M547 Stains to create custom colors. Mohawk Wood Stain Reducer S-15 M650-2507 can be used to reduce stain. Allow to dry (approximately 30 minutes) before sealing or topcoating. Clean up with mineral spirits.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545

INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user.

MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.