

DISTRIBUTED BY: Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033



Cynx 100H

100 Series HVLP General Purpose

The Lynx 100H is a high quality general purpose pressure feed sprayer. Designed with an all stainless steel fluid passage, this spray gun can be set up with low volume air caps for small HP compressor use which makes it perfect for on site jobs.

Lynx 100H

Features

Forged Aluminum Body

Stainless Steel Fluid Passages

Great for Onsite or Production applications

Available with the Low CFM 21-1090 Air Cap for Portability with On Site Jobs



1 Quart **Pressure Cup** (Aluminum) OL100H-303R2



1 Quart Pressure Cup (PPS) OL100H-PPSR2

Lynx 100H "HVLP Versatility"

Lunx

Available Outfits





Tank Outfits Include 25' Hose Assemblies and are available in 2.5 gal, 5 gal, 10 gal, 12.5 gal and 15 gal sizes. (Includes 25' Hose Assemblies)

Tank Outfits



Coating Atomization Technologies: 337 S. Arthur Ave. Louisville, CO 80027 Phone: 888.820.4498, Fax: 303.438.5708







Nozzle Chart for Lynx 100H					
Material Type	Fluid Orifice x Air Cap	Maximum Pattern Width	Pressure / Siphon		
Very Thin less than 16 sec. Zahn #2 inks, dyes, solvents, stains	0.5, 0.8 mm x 1090	10	P		
	0.5, 0.8 mm x 1092	11	P		
Thin 16 to 20 sec. Zahn #2 lacqers, enamels, primers, sealers	1.0, 1.2 mm x 1092	11	P		
	1.0, 1.2 mm x 1093	12	P		
Medium 21 to 30 sec. Zahn #2 automotive base coat enamels, primers, epoxies, urethanes, automotive clear coat	1.3, 1.4, 1.5 mm x 1093	12	P		
	1.3, 1.4, 1.5 mm x 1095	12	P		
	1.3, 1.4, 1.5 mm x 1097	13	P		
Heavy over 30 sec. Zahn #2 heavy body primers, high solid enamels, high solid automotive coatings, adhesives	1.6, 1.7 mm x 1095 1.6, 1.7 mm x 1097 1.6, 1.7 mm x 1195 1.6, 1.7 mm x 1197	12 13 13 14	P P P		

Air Caps for Lynx 100H						
Air Caps	Retaining Rings	Max Inlet Pressure	CFM @ Max Inlet Pressure			
21-1090		15 PSI	6 CFM @ 15 PSI			
21-1091		15 PSI	8 CFM @ 15 PSI			
21-1092	7	15 PSI	8 CFM @ 15 PSI			
21-1093	21-1001	18 PSI	10 CFM @ 18 PSI			
21-1094		33 PSI	13 CFM @ 33 PSI			
21-1095	_	50 PSI	20 CFM @ 50 PSI			
21-1097		50 PSI	20 CFM @ 50 PSI			
21-1195	Included	50 PSI	20 CFM @ 50 PSI			
21-1197	iliciadea	50 PSI	20 CFM @ 50 PSI			



Double Diaphragm Pumps

1:1 Double Diaphragm Units

Double Diaphragm **Specifications**

Flow Rate Adjustable: 0-12 GPM (45 LPM)

Suction Lift......20' (6.09m) Wet

Max. Particle Diameter......1.6 mm (.0625")

Port Size:



The 1/2" 1:1 Double Diaphragm (DD) pump from C.A. Technologies is an all stainless steel pump. This unit can be used as a transfer pump or a supply pump. The CAT DD pump offers a low pulsation valve design and integrated pressure regulator panel. Low maintenance with only 3 moving parts, this is a great unit for many applications. These pumps can be outfitted specifically for your needs. They are available as bare pumps as well as 5 and 55 gallon outfit. These outfits include wall mount or cart mount, 5 gallon pail and 55 gallon drum packages. The 5 gallon pail and 55 gallon drum configurations are offered with or without air agitation.

Double Diaphragm Pump Configurations





70-254 DOUBLE DIAPHRAGM PUMP (BARE PUMP)







70-1101-5 DOUBLE DIAPHRAGM PUMP WALL MOUNT (5 GALLON SIPHON)

70-1101-55 DOUBLE DIAPHRAGM PUMP WALL MOUNT (55 GALLON SIPHON)




70-1102-5 DOUBLE DIAPHRAGM PUMP CART MOUNT (5 GALLON SIPHON)

70-1102-55 DOUBLE DIAPHRAGM PUMP CART MOUNT (55 GALLON SIPHON)



70-1103 DOUBLE DIAPHRAGM PUMP PAIL MOUNT (5 GALLON)

70-1104 DOUBLE DIAPHRAGM PUMP PAIL MOUNT WITH AGITATOR (5 GALLON)



70-1105 DOUBLE DIAPHRAGM PUMP DRUM MOUNT (55 GALLON)

70-1106 DOUBLE DIAPHRAGM PUMP DRUM MOUNT WITH AGITATOR (55 GALLON)

Double Diaphragm Pump Accessories



Color Change Manifold 70-260 (3/8" Brass) 70-260SS (3/8" Stainless) 70-266SS (1/2" Stainless)



1/2" 5 Gal Siphon Hose Assy 1/2" 55 Gal Siphon Hose Assy 3/4" 5 Gal Siphon Hose Assy 3/4" 55 Gal Siphon Hose Assy 3/8" 5 Gal Siphon Hose Assy

74-520

74-524

74-530


74-531



Fluid Regulator 52-203



Pulse Chamber 70-271



Double Diaphragm Pumps



The 1/2" 1:1 Double Diaphragm (DD) pump from C.A.Technologies is an all stainless steel pump. This unit can be used as a transfer pump or a supply pump. The CAT DD pump offers a low pulsation valve design and integrated pressure regulator panel. Low maintenance with only 3 moving parts, this is a great unit for many applications.

C.A.Technologies DD pumps can be outfitted specifically for your needs. They are available as bare pumps as well as 5 and 55 gallon outfits. These outfits include wall mount or cart mount, 5 gallon pail and 55 gallon drum packages. The 5 gallon pail and 55 gallon drum configurations are offered with or without air agitation.


Specifications:

Inlet & Outlet - 1/2" NPT Air Inlet - 1/4" NPT Air Exhaust - 1/4" NPT

Part Sheet: Double Diaphragm Pump Sales Sheet: Double Diaphragm Pumps

Double Diaphragm Pumps					
Part #	Description	Agitator			
70-254	Bare Pump	None			
70-1101	Wall Mount Without Siphon Tube	None			
70-1101-5	Wall Mount With Siphon Tube (5 Gallon)	None			
70-1101-55	Wall Mount With Siphon Tube (55 Gallon)	None			
70-1102	Cart Mount Without Siphon Tube	None			
70-1102-5	Cart Mount With Siphon Tube (5 Gallon)	None			
70-1102-55	Cart Mount With Siphon Tube (55 Gallon)	None			
70-1103	5 Gallon Pail Mount	None			
70-1104	5 Gallon Pail Mount	Air			
70-1105	55 Gallon Drum Cover Mount	None			
70-1106	55 Gallon Drum Cover Mount	Air			
70-1107	55 Gallon Bung Mount	None			

Accessories





Company Information

About C.A.Technologies Members of WAGNER Group Contact C.A.Technologies

A Member of WAGNER Group



Coating Atomization Technologies 337 S. Arthur Avenue, Louisville CO 80027 Phone: (888) 820-4498 Fax: (303) 438-5708