

DISTRIBUTED BY: Pro Wood Finishes 14622 Southlawn Lane Rockville MD 20850 Ph: (301) 424-3033





hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame"

106° OPENING - 2 cams Traditional assembly of the door by screws



Stamped steel. Cup depth 11 mm (7/16"). Opening 106° degrees. Drilling distance (K) fixed at 2.5 mm (3/32"). Gap between door and frame (L) = 4.6 mm.

For overlays from 1/4"through 3/4" the "A" value (Reveal) = 8.3 mm for (21/64") square edge doors at 90° opening.

For overlays from 1" through 1-7/16" the "A" value (Reveal) = 5.2 mm for (3/4") square edge doors at 90° opening.







hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame" 106° OPENING - 2 cams







hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame" 106° OPENING - 2 cams







hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame" 106° OPENING - 2 cams







hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame" 106° OPENING - 2 cams







hinges automatic closing / face frame hinge / standard applications



Series S "Face-Frame" 106° OPENING - 2 cams

