

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Flat Oil Finish

M102-0424

13 oz. Net Wt. Aerosol

**Product Description:** Designed for oil-walnut and teak finishes. Spray over spot repairs to reduce gloss so as to blend in with the sheen of the surrounding finish. Can be used to produce a simulated oil finish over a previously stained surface.

Advantages:

1. Use to produce a simulated oil finish over previously stained surface
2. Reduce gloss of spot repairs to blend into surrounding finish

### Characteristics:

Weight per gallon: 6.51\*

Solids % (wt): 5.60\*

Solids % (vol): 3.56\*

Dry time: Air dry @ 77 F, 50% relative humidity

To touch: 7 minutes

To handle: 15 minutes

To recoat: 30 minutes

To rubout or package: 24 hours

PWR category: WTR

PWR Category limit: 1.5

PWR of product: 0.739\*

\*Includes propellant; values vary between colors  
All values theoretical; not intended to be exact  
QC specifications.

Package life: 3 years

Sheen: 10 degree flat

(Contains nitrocellulose resins, which tend to amber in color over time but does not affect coating performance)

All values theoretical; not intended to be exact QC specifications.

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection - X

**Directions:** Clean surface to be sprayed with Mohawk Wax Wash™ Remover. For best results, can temperature should be 65° - 90°. SHAKE WELL BEFORE USING for at least one minute after ball rattles to ensure color uniformity. Point opening of spray button toward object, holding can 12 to 14 inches away from surface to be coated. Press spray button firmly. Use steady, even strokes. Several thin coats give a better finish than one heavy coat. Allow coating to become tacky between coats. Clean spray button immediately by spraying with can upside down until no more product comes out. If clogged, remove spray button with a twisting motion and clean. Gently twist button onto can with opening turned away from you.

**Safety and Other Precautions:** Read MSDS for precautions before using product.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545

### INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user. **MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.