

PRODUCT INFORMATION



1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



PRODUCT: 80-7555 Series

DESCRIPTION: McCloskey®
Man O' War® Marine Spar Varnish Spray

FEATURES:

Exterior Spar Varnish provides maximum protection and long lasting beauty to exterior wood and other surfaces. Unlike traditional clear finishes which become brittle, crack and peel when used outdoors, this marine quality finish remains flexible and absorbs the expanding and contracting seasonal movement of the wood. Three coats are recommended.

WHERE TO USE:

Use on interior and exterior wood, metal and fiberglass surfaces.

SURFACE PREPARATION:

Surface must be clean, dry and free from all grease, wax and dirt. Sand surface smooth and remove sanding dust. Dull the gloss on previously finished surfaces by sanding lightly and removing sanding dust. Protect floor and surrounding objects from overspray with newspapers and masking tape.

80-7555 Series McCloskey Man O' War Marine Spar Varnish Spray

60° GLOSS: 30-40 Units (7555 Satin)
50-60 Units (7557 S/Gls)
80+ Units (7559 Gloss)

APPLICATION:

Use in a well ventilated area. Do not apply in temperatures below 50°F (10°C). Shake can vigorously for one minute after you hear agitator rattling. Hold can 8 to 10 inches from surface and aim spray head toward object. Spray back and forth with short fanning strokes. Allow overnight drying times between coats and sand with fine sandpaper or steel wool before applying additional coats.

CLEAN UP:

Clean nozzle by turning can upside down and spraying into refuse can or empty box for about 5 seconds to clear nozzle of material.

PACKAGING:

Sprays 6 Pack

Product Information Hotline:

1-800-345-4530

CAUTIONS:

CONTAINS NO CFC's - in accordance with Federal regulations which prohibit the use of CFC propellants in aerosols.

Contains: acetone, propane. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES EYE, NOSE, THROAT AND SKIN IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C). Contains propane as pressurizing agent. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH / MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.