

Mohawk

Finishing Products, Inc.

DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033

Product Data Sheet

AMALGAMATOR

M400- 000

AVAILABLE IN QUARTS, GALLONS

Product Description: Mohawk Amalgamator is a penetrating “padding agent” used to eliminate alcohol rings and heal checked or crazed finishes (alligator marks) by softening the old finish. Once the defect has been eliminated, it is recommended to apply Rapid Pad padding finish over the entire surface to seal Amalgamator.

Product Limitations:

1. Product must be topcoated to attain wearing qualities.

Characteristics:

Weight per gallon: 7.15 ± 0.1 lbs/gal

Flashpoint: 45F/7C

Dry time: Air dry @ 72F

To touch: 2 minutes

To topcoat: 10 minutes

Volatile Organic Compounds (VOC):

810 GPL, 6.7 lb/gal

Spec. Gravity: 0.86 ± 0.01

Boiling Range: 170F/77C

Non Volatile (wt): 6.0 ± 0.1%

Coverage: 70 sq. ft./gal

Package Life: 2 years

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 1.48 ± 0.1 lb/1 lb. solids

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Specifications: SHAKE WELL BEFORE USING.

Directions: First apply Amalgamator Solvent to the pad. Then add a little Amalgamator. Tap the pad in palm of hand to disperse the solution.

Apply in a circular motion. Do not stop with pad on surface, as this will cause an imprint.

Finish off by padding with the grain. Use Rapid Pad as a finish topcoat.

Safety Cautions: Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.

POISON: Contains Methanol. Cannot be made nonpoisonous. Harmful or fatal if swallowed. May be harmful if absorbed through the skin.

Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551