

## E-Z FLOW BURN-IN STICK M315/316 – (COLOR NUMBER)

Available in 2 inch and 7 inch lengths

---

**Product Description:** The Mohawk E-Z Flow Burn-in sticks are the benchmark of the furniture industry. With the excellent flow, leveling properties, and the clarity of the transparents, the sixty (60) color varieties makes the E-Z Flow Burn-in line the most adaptable to all repair situations.

### Advantages:

1. Excellent adhesion to the substrate.
2. Levels easily with no cup-out
3. Resists swelling and shrinkage from topcoats.
4. Exceptional clarity with transparent colors.

### Product Limitations:

1. Do not touch molten material. Serious burns may result.

---

### **Characteristics:**

\*Weight per gallon: 10.15 – 10.8 lbs./gal.

Flashpoint: None

\*Spec. Gravity: 1.23 – 1.30

Non Volatile (wt): 100%

Package Life: 3 years

Volatile Organic Compounds (VOC): 0.0

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.0 lb./1 lb. solids

\* Depending upon color

### HMIS:

Health: 0

Flammability: 0

Reactivity: 0

Personal Protection: A

## ***Specifications:***

### **Directions:**

1. Prepare the damaged area by removing loose wood fibers, splinters and other contaminants. Damage must be dry and free of oil and wax.
2. Allow the Burn-In Knife to become warm enough that the E-Z Flow stick will melt and flow into damage.  
Note: Mohawk M900-EK24FC Burn-In Knife can reach a maximum tip temperature of 300°F. A heat control unit allows the user ultimate control of knife temperature.
3. Select the E-Z Flow stick that most closely matches the background color.
4. Melt enough E-Z Flow stick on the knife blade to slightly overfill the damaged area.
5. Flow the melted E-Z Flow stick material into the damaged area. Do not hold the hot blade in the fresh fill, as this tends to create air entrapment.
6. Allow the fill to cool. Level the fill using conventional burn-in methods.

**Safety Cautions:** Contents are NON-FLAMMABLE and non-hazardous.

Avoid breathing hot vapor. USE ONLY WITH ADEQUATE VENTILATION. Local ventilation adequate.

Caution: Serious burns may result from handling molten material.

KEEP OUT OF REACH OF CHILDREN

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551