

DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033

Mohawk

Finishing Products, Inc.

Product Data Sheet

TWO MINUTE TOUCH-UP AND SOLVENT (BRUSHING LIQUID) M440-000 (BRUSHING LIQUID), M441-000 (SOLVENT)

Available in quarts

Product Description: The Mohawk Brushing Liquid is suitable for use in making repairs to damaged areas that do not lend themselves to conventional padding method systems. Blendal powders can be incorporated into the Brushing Liquid. The mixture can then be reduced with the Two Minute Touch-up Solvent for a lay flat to the wood color appearance.

Advantages:

1. Easy to use.
2. Will brush very free.
3. Dries quickly.
4. Excellent adhesion.

Product Limitations:

1. Designed for interior use only.

Characteristics: For Two Minute Touch-Up

Weight per gallon: 7.45 ± 0.05 lbs./gal.

Flashpoint: 41° F/5 c

Package Viscosity: 26-31 “ #2 Zahn cup

Dry time: Air Dry @ 72 F, 35% Relative Humidity

To touch: 5 minutes

To handle: 15 minutes

To sand: 30 minutes

To recoat: 60 minutes

Spec. Gravity: 0.906 ± 0.01

Boiling Range 169 F/76c

Non Volatile (wt.) 18.8 ± 0.5%

Coverage: 200 sq. ft./gal.

Package Life: 2 years

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.6 ± 0.01 lb/1 lb. Solids
lb/1 lb. solids

Volatile Organic Compounds (VOC): 720 grams/
Liter, 6.02 lb./gal.

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be clean and dry.

A clear touch-up material for brush touch-up work or running edges. Any Mohawk Blendal Powder Stain can be mixed with this clear liquid to achieve proper color. Sets up free from dust in two minutes.

Use **TWO MINUTE TOUCH-UP SOLVENT** to adjust viscosity and for cleaning up.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551