

BLOCK-OUT TONER

M103-7001 (BLUE), 7002 (GREEN), 7003 (ORANGE), 7004 (TRANS. ORANGE)

AVAILABLE IN 13 oz. AEROSOL

Product Description: Mohawk Tone Finish Block-Out Toner utilizes new technological color advances. Use Block-Out to uniform off-color spots on furniture of all types. Problems of redness, darkness or shading can be solved using Block-Out.

Advantages:

1. Permanent transparent colored lacquer coatings.
2. Color harmony and enhanced color tone can be achieved by using Block-Out colors. Orange will warm up cold colors, green and blue will neutralize red to produce brown shades.
3. Utilization of the basic principle of complimentary or supplementary colors and the interaction of light produces the desired effect.

Product Limitations:

1. For interior use only.

Characteristics:

Weight per gallon: 7.43 ± 0.1 lbs./gal.

Flashpoint: <0F/-17.8C

Package Viscosity: 23-25 seconds #1 Zahn cup

Dry time: Air dry @ 72F, 35% RH

To touch: 3 minutes

Tack free: 4 minutes

Dry to handle: 5 minutes

Dry to package: overnight

Volatile Organic Compounds (VOC):

Does not exceed 95%

Spec. Gravity: .89 ± 0.01

Boiling Range: -30F/-34C

Non Volatile (wt): 9.0 ± .5%

Package Life: 3 years

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.71 ± 0.1 lb/1 lb. solids

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface to be sprayed should be clean and dry. For best results, use only when can temperature is between 65°F and 90°F. Use steady even strokes while spraying. Spray lightly until desired intensity and tone is achieved. Block-Out finishes do not need recoating and can serve as a topcoat themselves.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.
Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:
Mohawk Finishing Products, Inc.
4715 STHWY 30
Amsterdam, NY 12010-7417
Phone: 518-843-1380
Fax: 518-842-3551