

Clear Wood Finish Interior Lacquer Sanding Sealer

Specially formulated sanding sealer for use with Clear Wood Finish Brushing Lacquer



DEFT® Interior Clear Wood Finish Sanding Sealer is specially formulated to precede the application of Clear Wood Finish Brushing Lacquer. The sanding sealer serves as the base coat and is designed to seal and protect the surface. *Deft* Lacquer sanding sealer is ideal for stained or bare wood surfaces, including furniture, floors, cabinets, doors and trim.

Proven Durability

- Applies easily with a brush, pad or roller
- Self-leveling formula
- Dry to touch in 30 minutes, ready for sanding in 1 hour
- Extremely easy to sand.

Plenty of Uses

Deft Clear Wood Finish Lacquer Sanding Sealer seals the wood and protects the surface. It's ideal for:

- Furniture
- Doors
- Trim
- Cabinets
- Paneling
- Molding
- Use on Rosewoods and other exotic hardwoods

Conformance Standard

VOC compliant – lower than Federal AIM



DISTRIBUTED BY:
Pro Wood Finishes
14622 Southlawn Lane
Rockville MD 20850
Ph: (301) 424-3033

DFT015	Sanding Sealer	Quarts, Gallons
DFT015S	Sanding Sealer	Aerosol†

Product Data

PRODUCT TYPE:	Nitrocellulose Lacquer
SHEEN:	DFT015 14-24 (60°)
VOLUME SOLIDS:	16.5 ± 1%
WEIGHT SOLIDS:	25 ± 1%
VOC*:	<680 g/L
WEIGHT/GALLON:	7.4 – 7.6
FLASH POINT:	53°F (11.67°C)
VISCOSITY* @77°F (25°C):	12 – 18 sec. EZ #3 (Zahn cup)
COVERAGE:	Up to 500 sq. ft./gal. (46.5 sq. m/3.78L) depending on surface texture and porosity.
Wet Film Thickness:	3.0 mils
Wet Microns:	76.2
Dry Film Thickness:	0.5 mils
Dry Microns:	12.7

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Touch:	30 minutes
Tack-Free:	60 minutes
To Recoat:	2 hours

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Clean all brushes and applicators with Lacquer Thinner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal on unused product. Do not pour down a drain or storm sewer.

†Patented Fanspray™ nozzles rotates to create a more precise vertical or horizontal fan spray pattern; allow for better control, less overspray and more even coverage.



Application Information

Stir thoroughly before using. Do not shake. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheets (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Application Equipment: Apply with a brush, paint pad or aerosol. This product must not be thinned or sprayed.

Application Method: Always apply with the grain of the wood using a smooth, even stroke. Use a quality bristle brush and avoid over-brushing since lacquers set up fast. For aerosols, please refer to the product label or MSDS for safety and detailed applications instructions.

General Surface Preparation

Surface must be clean and dry. Remove all loose and peeling paint, dirt, grease and any other surface contaminants.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health

Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

BARE WOOD: Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove all dust.

PREVIOUSLY COATED WOOD: If the clean surface is in good condition, sand with 180-220 grit sandpaper. Remove all dust. Test in a small area. If it wrinkles or lifts, strip to bare wood. If the finish is damaged or deteriorated, complete removal of the finish is recommended.

RECOAT: Sand with 180 to 220 grit sandpaper along the wood grain until smooth. Remove dust. Finish with *Deft* Clear Wood Finish Brushing Lacquer. Clear Wood Finish Lacquer Sanding Sealer should only be used as a base coat for lacquer finishes.

Limitations of Use

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

Clear Wood Finish Lacquer Sanding Sealer should only be used as a base coat for lacquer finishes.

Not recommended for floors.

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. WARNING! KEEP FROM HEAT OR FLAME. HARMFUL OR FATAL IF SWALLOWED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. CAUSES EYEBURNS. DO NOT GET IN EYES, ON SKIN OR CLOTHING. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. **VAPORS MAY CAUSE FLASH FIRE.** Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. **USE ONLY WITH ADEQUATE VENTILATION.** Do not breathe dust, vapors or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If air monitoring demonstrates, vapor/mist levels are above application above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes or on skin or clothing. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused containers in accordance with local, state and federal regulations. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN. NOT RECOMMENDED FOR EXTERIOR FOR FLOOR USES.**