

# Mohawk

Finishing Products, Inc.

# Product Data Sheet

## HEAVY BODIED SANDING SEALER

### M102-0491

AVAILABLE IN 13 OZ. AEROSOL

**Product Description:** The Mohawk Heavy Bodied Sanding Sealer has been reformulated for higher solids and faster build than ever before with exceptional blush resistance, excellent flow out and greater clarity. This sealer is truly dead flat in sheen (5 sheen or less).

### Advantages:

1. HAP's compliant.
2. Aerosol form – no extra equipment needed.
3. A unique ability to fill imperfections.
4. Good cold check resistance.
5. Low sheen (under 5 sheen) for low sheen finishes.
6. Greater clarity than typical with high build sealers.
7. Exceptional blush resistance.
8. Very good flow out.
9. Very high solids (23.24% by wt.) for maximum build per coat.
10. Low sheen (less than 5 sheen)
11. MIR and VOC compliant

### Product Limitations:

1. Designed for interior use only.
2. Intended as a high build, low sheen repair sealer, or for finishing use.

---

### **Characteristics:**

Weight per gallon: 7.62 ± 0.1 lbs./gal.

Flashpoint: < 0 F/-17.8 c

Package Viscosity: 31 seconds #1 Zahn cup

Dry time: Air Dry @ 72 F, 35% relative humidity

To touch: 2 minutes

To handle: 5 minutes

To sand: Light coat 3 min., full wet coat 8 min.

To recoat: Touch up 10 min., refinish 30+ min.

Solids weight: 23.24% (without propellant)

Solids volume: 16.49% (without propellant)

Volatile Organic Compounds (VOC): Does not exceed 95% VOC

Sheen: less than 5

Spec. Gravity: .906 ± 0.01

Boiling Range: -30 F/-34 c

Non Volatile (wt): 13.34 ± 0.2% (Sealer)

Package Life: 3 years

VHAP's: 0.74 ± 0.05 lb./1 lb. solids

Air Quality Data: Non-Photochemically Reactive

HMIS:

Health: 2

Flammability: 4

Reactivity: 0

Personal Protection: B

***Specifications:***

Directions: SHAKE WELL BEFORE USING. Surface should be clean, dry, finish sanded with a wood moisture content of 6-8% maximum. For best results, use only when can temperature is between 65 °F and 90°F. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545