



## NO BLUSH™ PLUS RETARDER

### TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M103-0475	NO BLUSH™ PLUS RETARDER

#### PRODUCT DESCRIPTION:

Mohawk's No Blush™ Plus Retarder contains a special solvent blend designed to eliminate blushing (hazy whiteness or cloudiness due to trapped moisture) in lacquer finishes.

#### ADVANTAGES:

1. Easy to use.
2. Very effective.
3. Controlled results.

#### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Penetrating solvent retarder
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	7.45 lbs/gal
Solids by Volume	0.00 ±1%
Solids by Weight	0.00 ±1%
Flash Point	24.80 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l as packaged)	892.62 g/l
Coating VOC (Lb/Gal)	7.45 lbs/gal
Material VOC (g/l)	892.62 g/l
Material VOC (Lb/Gal)	7.45 lbs/gal
#VOC/#Solid	0.00 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.00
Spread Rate	0.00 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To touch: 20 min, To package: overnight
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

**DIRECTIONS:**

SHAKE WELL for at least one minute after ball rattles. Can temperature should be between 65° and 90° F. Hold can 12 to 14 inches away from surface to be coated. Press spray button firmly. Spray in thin coats to avoid excessive drying times. Wait a few minutes to see if problem is solved before spraying another coat. Clean spray button after use by turning can upside down and pressing spray button until no more product comes out.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.