

# PosiTector® 200 Series

## All Gages Feature...

### Simple

- Ready to measure—no adjustment required to measure most coatings
- RESET feature instantly restores factory settings

### Durable

- Solvent, acid, oil, water and dust resistant—weatherproof
- Shock-absorbing, protective rubber holster with belt clip
- Two year warranty on body AND probe

### Accurate

- Responsive transducers provide fast, accurate readings
- Certificate of Calibration showing traceability to NIST or PTB included
- Proven non-destructive technique conforms to ASTM D6132 and ISO 2808

### Versatile

- PosiTector body accepts all PosiTector probes easily converting from a coating thickness gage to a surface profile gage, dew point meter or wall thickness gage
- Flip display enables right-side-up viewing
- Uses alkaline or rechargeable batteries (built-in charger)

### Powerful

- Continually displays average, standard deviation and min/max thickness
- USB port for connection to a Mac/PC and to supply continuous power
- Every stored measurement is date and time stamped
- PosiSoft USB Drive—stored readings, graphs and screen captures can be accessed using universal PC/Mac web browsers or file explorers. No software required.
- Includes PosiSoft Suite of solutions for analyzing and reporting data



### Select from a variety of measurement ranges

Probes	200B	200C	200D
<b>Typical Applications</b>	Polymer coatings on wood, plastic, etc.	Coatings on concrete, fiberglass, etc.	Thick, soft coatings such as polyurea, asphaltic neoprene, very thick polymers, etc.
<b>Measurement Range*</b>	13–1000 µm 0.5–40 mils	50–3800 µm 2–150 mils	50–7600 µm 2–300 mils
<b>Accuracy</b>	+/- (2 µm + 3% of reading) +/- (0.1 mil + 3% of reading)		+/- (20 µm + 3% of reading) +/- (1 mil + 3% of reading)
<b>Minimum Layer Thickness^</b>	13 µm 0.5 mil	50 µm 2 mils	500 µm 20 mils

\*Range limits apply to polymer coatings. D probe—polyurea range is 50–5000 µm (2–200 mils).


^For multiple-layer applications only. Dependent on material being tested.

### Select Standard or Advanced Features

#### Standard Models

*Includes ALL features as shown on left plus...*

- Measure the total thickness of a coating system
- Backlit monochrome display with transfective technology
- Storage of 250 readings



**All gages come complete** with body and probe, ultrasonic gel, precision plastic shims, protective rubber holster with belt clip, wrist strap, 3 AAA batteries, instructions, nylon carrying case with shoulder strap, protective lens shield, long form Certificate of Calibration traceable to NIST or PTB, USB cable, PosiSoft.net account, two year warranty on body and probe.

**Size:** 135 x 61 x 28 mm (5.25" x 2.4" x 1.1")

**Weight:** 140 g (4.9 oz.) without batteries  
Conforms to ASTM D6132 and ISO 2808



**DeFelsko®**  
The Measure of Quality

DeFelsko Corporation • 800 Proctor Ave. • Ogdensburg, New York 13669-2205 USA  
Toll Free 1-800-448-3835 • Tel: +1-315-393-4450 • Fax: +1-315-393-8471  
techsale@defelsko.com • www.defelsko.com

©DeFelsko Corporation USA 2015. All Rights Reserved. Technical Data subject to change without notice. • Printed in USA • PSL.v.LW/W1509

**Made in U.S.A.**