

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Spray Adhesive (10 oz. aerosol)

M103-0195

Product Description: Spray Adhesive offers a fast tack time, which enables general purpose bonding on a wide variety of substrates, high bond strength and may be used to create a temporary or permanent bond. Its unique formula prevents soak in of the adhesive on porous surfaces. Spray Adhesive does not contain Methylene chloride and meets Federal & State VOC requirements.

Advantages:

1. Meets Federal & State VOC requirements
2. Repositionable
3. All purpose mist spray
4. High bond strength
5. Fast tack
6. Bonds polyurethane foam, wood, plastic, leather, paper and fabric

Characteristics:

Solids: 17 % \pm 2%

VOC content: Less than 65%

Heat resistance: Maximum service temperature of cured adhesive is 120 deg F.

Bonding time: 15 seconds – 5 minutes

Package life: 1 year from date of shipment

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

Specifications:

Directions: SHAKE WELL BEFORE USING.

Permanent Bonds: Apply to both surfaces to be bonded, spraying from a distance of 6 to 8 inches while keeping the can moving for even application. Allow adhesive to dry to a tack and then bond.

Temporary Bonds (repositionable): Apply to only one surface. Allow to dry to a tack and then bond.

IMPORTANT: After use, invert can and press nozzle to clear valve and spray tip. Clean with petroleum solvent if clogged. Not recommended for unsupported vinyl fabric. Certain plastic and elastomeric substrates can exhibit bond failure due to plasticizer migration. Combinations of high temperature and humidity can promote bond failure. Testing of production parts in typical operating environments for compatibility is recommended.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000 Phone: 1-800-545-0047
Hickory, NC 28603 Fax: 1-800-721-1545

INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user. **MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.